

Training for the Real World®

SIMUNITION®

CONVERSION KIT
5.56MM HK416 AND VARIANTS

The Simunition® conversion bolt allows the FX® Marking Cartridges and the SecuriBlank® to be fired safely from the user's own service weapon. This operator installed kit, precludes the inadvertent firing of live ammunition and ensures the proper operation and cycling of the weapons through a direct blow back action.

The conversions kits are an integral part of the FX® training system along with the FX® marking cartridges, the FX® protective equipment and the Simunition® Scenario Instructor Safety Course.



Weapons can be quickly converted back to operational status once training is over. The kits are made from the same type of high-strength materials as duty weapons and are designed with various safety features to help preclude the firing of lethal, live ammunition.

TECHNICAL SPECIFICATIONS

Type	Conversion Bolt for HK416/C7/C8/M4/M16/Sig 516
Caliber	5.56mm
Function Mode	All Firing Modes
Color	Blue Markings for Visual Safety
Safety Features	All kits tested 100% to preclude live fire of NATO 5.56mm ball
Product Number	5311350
Warranty	5 years or 10,000 rounds fired (refer to www.simunition.com for warranty conditions)
Patent Number	US 6,625,916 B1
5.56 mm FX® Magazine	PN: 5310860SP
Blue Barrel Indicator	PN: 5308499SP

SIMUNITION, Safety as The Standard™

SIMUNITION

www.simunition.com

www.gd-otscanada.com

Trademarks and registered trademarks of General Dynamics Ordnance and Tactical Systems-Canada are denoted by TM and ® respectively.

© 2017 General Dynamics Ordnance and Tactical Systems

Distributed worldwide exclusively through the Simunition® network

Canada (Home office)
GENERAL DYNAMICS
Ordnance and Tactical Systems-Canada
5 Montée des Arsenaux
Repentigny, Québec
Canada J5Z 2P4
Tel.: 1-450-581-5999
Fax: 1-450-581-0231
Management System Certified
ISO 9001, ISO 14001 & OHSAS 18001

USA
GENERAL DYNAMICS
Ordnance and Tactical Systems
Simunition Operations
P.O. Box 576
Avon, CT 06001-0576 USA
Tel. USA only: 1-800-465-8255
Tel.: 1-860-404-0162
Fax: 1-860-404-0169



5-2017