

**SIMUNITION®**

# 7.62X 51MM FX® MARKING CARTRIDGE

AS REAL AS YOU CAN GET™



Simunition® is the world leader in safe, realistic, interactive and combat training solutions.

The 7.62mm FX® Marking Cartridge is designed using the Simunition® patented reduced energy technology and works with a Simunition® Certified Conversion Kit, increasing safety and ensuring proper weapon functioning.

## THE 7.62MM FX® MARKING CARTRIDGE HAS MANY IMPRESSIVE FEATURES:

- Designed for military, law enforcement and approved range programs
- Non-toxic and non-lethal cartridge
- Easily washable with cold water
- Available in red and blue, FX® Non-Marking also available
- Similar impact penalty as the 9mm FX® Marking Cartridge
- Visible impacts allow accurate assessment of simulated lethality
- Tactically accurate to 30m (100ft)
- Convenient for training any time, any place, indoors and outdoors
- Used with FX® 9000 series Protective Equipment

## IN ADDITION, THE SIMUNITION® CONVERSION BOLT:

- User-installed temporary weapon conversion; no tool required
- Safe design diminishes the possibility of firing lethal ammunition
- Works with the user's service weapon without adding extra weight
- Realistic weapon functioning capable of firing in semi-auto and fully-automatic modes

## THE 7.62MM FX® MARKING CARTRIDGE IS IDEAL FOR TRAINING:

- Reality-based, force-on-force interactive scenarios
- Force-on-target training; practically anywhere
- Weapon safety handling training
- Urban fighting (MOUT/FIBUA)
- Anti-terrorism
- Convoy protection tactics
- Compatible with laser-based training simulators
- Patrol exercises
- Close-Quarter Battle (CQB)
- Shoot/no shoot decisions
- Individual/team situations
- Room/building/trench clearing
- Mission rehearsal



## FX® SCENARIO INSTRUCTOR AND SAFETY CERTIFICATION COURSE

- Highly qualified professional trainers
- Courses are offered worldwide. Visit [www.simunition.com](http://www.simunition.com) for more information on available courses

## COMPONENTS

Designation	FX® Marking Cartridge
Caliber	7.62 x 51mm
Projectile mass*	Approx. 0.4g (6grains)
Projectile material	Plastic projectile that deforms upon impact releasing marking compound
Cartridge case	Aluminum
Marking compound	Non-toxic marking compound washable with cold water
Marking colors	Red and blue
Primer	ToxFree® primer
Propellant	Single or double-base smokeless powder

## BALLISTIC DATA\*

Average muzzle velocity at 21°C (70°F)	Approx. 140-160m/s (459-524fps); depending on the weapon used
Typical Accuracy* (indoor) at 21°C (70°F)	Can achieve 20cm (8in) at 30m (100ft) shoulder fired, depending on the weapon used
Maximum range, no wind, no elevation	Approx. 150m (492ft)
Penetration in 20% gelatin at 1m (3ft)	None
Impact energy (at 3.5m)	Approx. 3.92-5 joules
Ballistic match	Nominal -20cm (-8in) at 30m (100ft) shoulder fired

## TERMINAL EFFECT

Lethality	Non-lethal bruises, welts or scrapes
-----------	--------------------------------------

## USE

General	For use with Simunition® conversion kit only
Operational temperature range	-8°C (18°F) to +40°C (104°F)
Mandatory Personal Protective Equipment, Simunition® approved	Head, throat, groin and full body covering, including hands
Firing modes	Single shot, burst and fully-automatic

## STORAGE

Recommended storage	Cool, dry environment, 25°C (77°F) max
Shelf life	Five years, in original packaging
Warranty	One year

## WEAPONS

The ammunition will function (feed and cycle) in a wide variety of converted weapons. Please contact Simunition® to validate weapon make and model. Please refer to [www.simunition.com](http://www.simunition.com) for a detailed listing of all available models.

\* Dimensions, weights and velocities are nominal. Values are dependent on type of weapon, barrel length, rifling, cleanliness, and shall not be used for lot acceptance.

## GUIDELINES FOR USE:

- Intended only for supervised training conducted in accordance with Simunition® safety training protocols by law enforcement, military and Simunition® approved Commercial Range Programs (in select markets)
- Use only under the direction of a qualified Simunition® Training Safety Officer
- Use only in firearms which have been converted with a Simunition® Conversion Kit
- Users must wear approved FX® Personal Protective Equipment (head, throat and groin protection) and full-body covering, including hands
- Simunition® requires a minimum 1m (3ft) stand-off distance when firing 7.62mm FX® Marking Cartridge at protected personnel
- Clearly identify converted weapons with FX® blue tape on the barrel, grip and magazines
- General Dynamics assumes no responsibility for injuries, loss or damage resulting from misuse of this ammunition

SIMUNITION, SAFETY AS THE STANDARD®  
[WWW.SIMUNITION.COM](http://WWW.SIMUNITION.COM)



Trademarks and registered trademarks of General Dynamics Ordnance and Tactical Systems-Canada are denoted by™ and® respectively.

Distributed worldwide exclusively through the Simunition® network

◆ INFORMATION PUBLISHED HEREIN IS SUBJECT TO CHANGE  
 AT MANUFACTURER'S DISCRETION WITHOUT NOTICE

CANADA (HOME OFFICE)

**GENERAL DYNAMICS**  
 Ordnance and Tactical Systems-Canada

1 450 581 5999  
 Management System Certified  
 ISO 9001, ISO 14001 & ISO 45001

↑ [www.gd-otscanada.com](http://www.gd-otscanada.com)

USA

**GENERAL DYNAMICS**  
 Ordnance and Tactical Systems

1 860 404 0162  
 1 800 465 8255 (USA Only)

↑ [info@simunition.com](mailto:info@simunition.com)